

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
13 January 2005 (13.01.2005)

PCT

(10) International Publication Number  
**WO 2005/004299 A1**

(51) International Patent Classification?: **H02H 9/02,**  
**H01L 39/16**

Anthony [AU/AU]; 5 Glenda Place, Mount Kuring-Gai,  
NSW 2080 (AU).

(21) International Application Number:  
PCT/AU2004/000906

(74) Agent: SHELSTON IP; 60 Margaret Street, Sydney NSW  
2000 (AU).

(22) International Filing Date: 6 July 2004 (06.07.2004)

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003903489 7 July 2003 (07.07.2003) AU

(71) Applicant (*for all designated States except US*): METAL  
MANUFACTURES LIMITED [AU/AU]; 15 Merriwa  
Street, Gordon, NSW 2072 (AU).


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): DARMANN, Francis,

[Continued on next page]

(54) Title: SUPERCONDUCTOR CURRENT LIMITING SYSTEM AND METHOD



(57) Abstract: A fault current limiter for limiting current faults in an electrical network comprising: a series of phase coils located adjacent a superconductive coil for fault current limiting phase faults within the network; a series of neutral coils located adjacent the superconductive coil for fault current limiting neutral earthing faults in the electrical network.

- Neutral earthing coils, for limiting earth fault currents by a greater than three phase symmetrical fault currents.
- Three sets of AC coils for limiting symmetrical three phase faults - Ident
- Cryostat
- HTS coil and support
- Footprint
- Iron core leg, diameter: d, window: w x h

WO 2005/004299 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*